

STANDARD ACCESSORIES

# BULL-LINE PULL TAPE WOVEN POLYESTER FIBER

- ▶ High performance Stiff-Tape™ lubricated coating
- ▶ Best burn-through (conduit cutting) resistance
- ▶ Excellent blowability into conduit
- ▶ Accurate sequential foot or meter markings every 2 feet
- ▶ Can be pre-installed into conduit
- ▶ Exceeds requirements of Bellcore GR-356-CORE
- ▶ Available on reels in a wide variety of lengths



<b>TENSILE STRENGTH RANGE</b> 500lb – 6,000lb (227kg – 2,727kg)
<b>APPROXIMATE WIDTH</b> 1/4" – 1 1/8" (6mm – 28mm)

STOCKING INFORMATION WOVEN POLYESTER PULL TAPE



DESCRIPTION	LENGTH	REEL SIZE	TYPE	PART #
WP05 tensile: 500lb width: 1/4" (6mm) weight/ft: 0.0034lb	3000'	12"	P	20000044
	5000'	12"	P	20000045
	10000'	14"	P	20000043
WP10 tensile: 1,000lb width: 7/16" (11mm) weight/ft: 0.0063lb	3000'	12"	P	20000047
	5000'	14"	P	20000048
WP12 tensile: 1,250lb width: 1/2" (13mm) weight/ft: 0.0077lb	500'	8"	W	20000139
	1000'	8"	W	20000138
	1500'	12"	P	20000394
	3000'	12"	P	20000052
	5000'	14"	P	20000054
	10000'	16"	P	20000051
	20000'	24"	W	20005113
	available in meters	900m	12"	P
WP18 tensile: 1,800lb width: 5/8" (16mm) weight/ft: 0.0105lb	1000m	13"	P	20000406
	2000m	16"	P	20002199
	500'	8"	W	20000142
WP18 tensile: 1,800lb width: 5/8" (16mm) weight/ft: 0.0105lb	1000'	12"	P	20000065
	1500'	12"	P	20000395
	3000'	13"	P	20000068
	5000'	16"	P	20000070
	6500'	16"	P	20000152
	10000'	18"	P	20000389
	12000'	22"	P	20000383

DESCRIPTION	LENGTH	REEL SIZE	TYPE	PART #
WP18 tensile: 1,800lb width: 5/8" (16mm) weight/ft: 0.0105lb available in meters	900m	13"	P	20000262
	900m	14"	WB	20000128
	1000m	14"	P	20000066
	2000m	18"	P	20003875
WP25 tensile: 2,500lb width: 3/4" (19mm) weight/ft: 0.0142lb	500'	8"	W	20000143
	1000'	12"	P	20000073
	1500'	12"	P	20000075
	1800'	14"	P	20003519
	3000'	14"	P	20000077
	5000'	16"	P	20000080
	6000'	18"	P	20002183
	6500'	18"	P	20000082
	10000'	24"	W	20000074
	available in meters	900m	18"	WB
WP40 tensile: 4,000lb (1,818kg) width: 7/8" (22mm) weight/ft: 0.0264lb	1000m	16"	P	20005022
	1800m	18"	WB	20003872
	2000m	18"	P	20005178
	2000m	18"	WB	20000076
	1000'	13"	P	20000153
	3000'	16"	P	20000161
WP60 tensile: 6,000lb (2,727kg) width: 1 1/8" (28mm) weight/ft: 0.0396lb	5000'	22"	P	20000160
	500'	12"	P	20000144
	1000'	14"	P	20000154
	1500'	16"	P	20002182
	2500'	18"	W	20000363
	3000'	18"	W	20000149
	5000'	24"	W	20000321
	6000'	24"	W	20000165

W=Wood P=Plastic WB=Wood Boxed  
all tape widths are approximate



An Orbia Connectivity Solutions business.

+1 800 847 7661  
WWW.DURALINE.COM



STANDARD ACCESSORIES

# BULL-LINE PULL TAPE SHIPPING INFORMATION



polyester



locatable



aramid



## SHIPPING INFORMATION ALL TAPE STYLES

REEL SIZE	REEL WEIGHT (LBS)	REELS/PALLET	PALLET SIZE
8" Wooden	1.5	100	45" x 45"
12" Plastic	2.2	48	45" x 45"
13" Plastic	2.3	36	45" x 45"
14" Plastic	3.5	36	45" x 45"
14" Wooden	4.5	36	45" x 45"
14" Wooden Boxed	4.5	36	45" x 45"
16" Plastic	4.4	18	45" x 45"
18" Plastic	5.0	10	45" x 45"
18" Wooden	7.8	10	45" x 45"
18" Wooden Boxed	7.8	8	45" x 45"
22" Plastic	7.4	8	45" x 45"
24" Wooden	14.0	4	45" x 45"



An Orbia Connectivity Solutions business.

+1 800 847 7661  
WWW.DURALINE.COM



# BULL-KNOT JOINING PROCEDURE

The following joining procedures for Bull-Line® Pull Tape were developed for tying two lengths of Bull-Line™ together or tying one length of Bull-Line® to a pulling swivel or pulling eye. The Bull-Knot was developed to be simple to tie yet provide consistent high strength. It is compact in size which minimizes hangup when pulling through the conduit system. In laboratory tensile testing and actual field use, the Bull-Knot has proven to be more reliable and outperforms "bowline" and other more recently developed pull tape knots. The Bull-Knot also works well on lubricated Bull-Line®.

## JOINING TWO LENGTHS OF BULL-LINE®



**STEP 1:** Double up 12 inches of Bull-Line®.



**STEP 2:** Tie a loose overhand knot.



**STEP 3:** Retrace the original overhand knot with a double strand of the adjoining tape end.



**STEP 4:** Keep the flat surface in continuous contact between the two tape lengths.



**STEP 5:** Pull slack out evenly from both ends.



**STEP 6:** Wrap completed Bull-Knot ends with vinyl tape.

## JOINING ONE LENGTH OF BULL-LINE®



**STEP 1:** Double up 24 inches of Bull-Line® end to be joined to the swivel or pulling eye.



**STEP 2:** Tie a loose overhand knot in the double strand, about 18 inches away from the free tape end.



**STEP 3:** Thread the free end through the pulling eye or swivel.



**STEP 4:** Retrace the original overhand knot with the double stranded free end.



**STEP 5:** Keep the flat surface in continuous contact between the two doubled tape lengths. Pull slack out evenly from both ends and wrap completed Bull-Knot ends with vinyl tape.

