

# FEEDER MC

## XHHW-2 / 600 Volt Copper

Using Feeder MC cables help contractors reduce costs on conduit installations while providing armored power solutions for high-occupancy structures such as hotels and office buildings.



### Product Overview

Feeder MC is easy to work with and eliminates the risk of damage when installing in tight spaces with multiple bends, saving time and money on installation costs.

- 3 or 4 stranded conductors with heat and moisture resistant cross-linked polyethylene (type XHHW-2) insulation
- Green or bare ground conductor
- Cable core covered with binder tape and aluminum or galvanized steel interlocked armor
- Jacket available upon request
- Cabled with suitable fillers when required

### Applications

- Cost-effective replacement for conduit and wire
- Service, branch, and feeder circuits
- Commercial, industrial, and utility applications
- Places of assembly with more than 100 occupants
- Suitable for use in hazardous locations:  
Class I, Division 2 & Class II, Division 2

## STANDARDS

- UL 1569
- ICEA S-95-658/NEMA WC 70
- Cable Tray Rated
- NEC Article 330  
(can be messenger supported)
- Flame Rated: 2-hour Firewall
- Temperature Rated at 90°C Wet/Dry
- Color Code: 4 Conductor  
- Black, Red, Blue, and White (8 AWG - 1 AWG)  
- Method 4 (1/0 AWG and larger)
- Ground  
- Green Ground (8 AWG - 1 AWG)  
- Bare Ground (1/0 AWG and larger)
- RoHS Compliant



For more information, please contact your Omni Cable Account Manager.

Atlanta • Boston • Charlotte • Chicago • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle • St. Louis • Tampa