







Omni Cable has signed agreements with both Eaton and Schneider Electric to serve as an authorized genuine source of their Eaton® and Square D^{TM} circuit breakers for select electrical distributors.

Availability

Omni Cable now sells Eaton® and Square D™ circuit breakers to electrical distributors, providing them with authorized, safe, and reliable products through a single source. Omni Cable is an extension of your warehouse with an extensive inventory of circuit breakers and accessories. Circuit breakers are available 24 hours a day, 365 days a year and shipped the same day.

Accessibility

It is all about safety when purchasing an AUTHENTIC product from an AUTHORIZED source. Unauthorized sources rely on deception and aggressive pricing. Identifying counterfeit products is extremely difficult. They are made with inferior materials, inaccurate manufacturing processes, and without functional or safety testing.

Traceability

An authentic product is only sold through an authorized source who can provide full TRACEABILITY. Purchasing products from unauthorized sources significantly increases your risk of receiving counterfeit, altered, tampered, or refurbished products. Unauthorized sources cannot provide traceability.

Don't expose your company to increased RISK and LIABILITY by purchasing suspect products from unauthorized sources. Your business reputation is on the line, so don't put your customers in an unsafe environment and exposing your company to unnecessary liability. Products purchased through unauthorized sources do not carry the factory warranty which leaves the distribution channel open to liability.

Circuit Breakers

Line Card



Applications

Types of equipment where circuit breakers are installed - Commercial Switchboards, Panelboards, Motor Control Centers, and Control Panels/Enclosures. Residential Loadcenters and Meter Centers.



Series C

G-Frame

Amperage Range: 15-100

F-Frame (EHD, FDB, FD, HFD, FDC, EDB, EDS, ED, EDH, EDC)

Amperage Range: 10-225

JD-Frame

Amperage Range: 70-250

K-Frame

Amperage Range: 100-400

LD-Frame

Amperage Range: 300-600

MDL-Frame

Amperage Range: 400-800

Series G

EG-Frame

Amperage Range: 15-125

JG-Frame

Amperage Range: 50-250

LG-Frame

Amperage Range: 250-600

NG-Frame

Amperage Range: 800-1200

RG-Frame

Amperage Range: 1600-2500

Specialty Circuit Breakers

Motor Circuit Protectors (MCP) Amperage Range: 3-1200 600V Direct Current (DC) Amperage Range: 15-3000

Photovoltaic/Solar DC Amperage Range: 30-600

High Instantaneous Circuit Breaker

Amperage Range: 125-400

Engine Generator

Amperage Range: 15-1200 Definite Purpose (HVAC) Amperage Range: 15-800

Miniature Circuit Breakers

BAB-Frame

Amperage Range: 10-125

QBH-Frame

Amperage Range: 15-125

Residential Circuit Breakers

BR-Frame (Plug-in) Amperage Range: 10-150 CH-Frame (Plug-in) Amperage Range: 10-125

Miniature Circuit Breakers

QOB Frame (Bolt-on) Amperage Range: 10-150

QO Frame (Plug-in) Amperage Range: 10-200

QOU Frame (Cable in/out) Amperage Range: 10-125

HOM Frame (Plug-in) Amperage Range: 10-200

Molded Case Circuit Breakers

E-Frame

Amperage Range: 15-125

F-Frame

Amperage Range: 15-100

K-Frame

Amperage Range: 70-250

D-Frame

Amperage Range: 150-600

LA-Frame

Amperage Range: 70-400

Specialty Circuit Breakers

Motor Circuit Protectors Amperage Range: 1.5-1200 500 Vdc Circuit Breakers Amperage Range: 30-1200

Photovoltaic (Solar) Amperage Range: 50-500

Mission Critical J & L Frames

Amperage Range: 70-600

by Schneider Electric PowerPact TM Molded

B-Frame

Amperage Range: 15-125

Case Circuit Breakers

H-Frame

Amperage Range: 15-150

J-Frame

Amperage Range: 50-250

Q-Frame

Amperage Range: 70-250

L-Frame

Amperage Range: 125-600

M-Frame

Amperage Range: 300-800

P-Frame

Amperage Range: 400-1200

R-Frame

Amperage Range: 800-3000